

DIN A4 ADF- & Flachbett-Dokumentscanner

KV-SL3066

Workgroup-Scanner / 65 ppm



KEY FEATURES

- ADF-/Flachbettscannen (DIN A4)
- Scannen auf Tastendruck
- Mehrfach-Zuschnitt
- ICP Express (Image Capture Plus Express)
- Bis zu 65 ppm Scangeschwindigkeit

Ultraschneller Mehrzweckscanner für ADF/Flachbettscannen

- Durch Kombination von automatischem Dokumenteneinzug (ADF) und Flachbettscannen größtmögliche Flexibilität und Effizienz
- Ultraschnelles Scannen von 65 Seiten/Minute bzw. 130 Bilder/Minute (45 Seiten/Minute bzw. 90 Bilder/Minute beim KV-SL3056)
- Tägliches Scanvolumen von 8.000 Blatt (6.000 Blatt beim KV-SL3056)
- Einfaches kontinuierliches Scannen über ADF und Vorlagenglas
- Scannen unterschiedlicher Vorlagen über beide Quellen

- Intuitive Bedienung und einfache Anpassung der Einstellungen mit der Software ICP Express (Image Capture Plus Express)

Mit den beiden Modellen der KV-SL30-Serie von Panasonic können Sie Informationen noch leichter als bisher scannen, austauschen, speichern und sichern.

Beide Modelle – der KV-SL3066 und der KV-SL3056 – sind in Bezug auf Schnelligkeit, Flexibilität und Funktionsumfang unschlagbar und bieten größere Profitabilität und geringere Gesamtbetriebskosten.



SPECIFICATIONS

Scanning Face	Duplex
Scanning Method	Color CIS (600 dpi)
Scanning Resolution	[ICP, TWAIN] 50 - 600 dpi (1 dpi step) and 1200dpi (software), [ISIS] 100 - 600 dpi (1 dpi step) and 1200dpi (software)Optical: 300 dpi / 600 dpi (Automatic switch)
Double Feed Detection	Ultrasonic (The length of documents that can be detected is 70 mm or more.)
Image Output	Binary 1-bit, Grayscale 8-bit, Color 24-bit, MultiStream (Color & Binary or Gray & Binary)
Internal Video Processing	1,024 levels (10-bit)
Tonal Gradation	Binary, Grayscale, Color, MultiStream: Binary & Grayscale, Binary & Color
Image Compression	MH, MMR, JPEG
Binary Mode Halftone	Dither, Error Diffusion
Image Control	Auto preview, Auto rescan, Deskew/Crop, Automatic Brightness Adjustment, Multi Colour Drop Out, Dynamic Threshold, White Level From Paper, Image Emphasis, Gamma, Automatic Separation, Noise Reduction
Other Functions	Barcode detection, Length Control, Patchcode Detection (Kodak-2, Kodak-3, Kodak-T), Control Sheet detection, Long Paper, Double Feed Skip
ADF Documents Size	Feeding size: Only 1 page 48×54 mm to 216 mm × No Limited (1.9×2.1 in. to 8.5 in. × No Limited) (Using "Long Paper") When using ADF: 48×54 mm to 216 mm × 356 mm (1.9×2.1 in. to 8.5 in. × 14 in.)
ADF Documents Thickness	Paper 0.04 - 0.5 mm (1.6 - 19.7 mils) ISO Card 0.76 mm (30.0 mils) Emboss card up to 1.4mm(0.055in.) Bound documents*1 2.6 mm (102.4 mils) *1: Use the dedicated carrier sheet Note: 1 mil = 0.001 in.

ADF Documents Weight	20 - 413 g/m2 (5 - 110 lbs.)
Flatbed Paper Size	Maximum size: 216 × 297 mm (8.5 × 11.69in.)
Feed Tray Capacity	100 sheets: 80 g/m2 (21lbs.) , A4 or Letter, High-quality woodfree paper/3 hard cards (ISO 7810 ID-1)
Roller Replacement	250,000 sheets
Supported Operating System	Windows XP SP3 (32bit), Windows Vista SP2 (32bit/64bit), Windows 7 (32bit/64bit), Windows 8 (32bit/64bit), Windows 8.1 (32bit/64bit), Windows 10 (32bit/64bit), Windows Server 2003 SP2 (32bit/64bit), Windows Server 2003 R2 SP2 (32bit/64bit), Windows Server 2008, Windows Server 2008 SP2 (32bit/64bit), Windows Server 2008 R2 SP1 (64bit), Windows Server 2012 (32 / 64-bit), Windows Server 2016 (32 / 64-bit), Windows Server 2019 (32 / 64-bit), Mac OS X 10.8-10.11, macOS 10.12-10.15, Linux RedHat Enterprise Desktop 6/7, Ubuntu 12/14/15/16/17/18/19
Interface	USB 2.0
External Dimensions (W x D x H)	300 x 650 x 308 mm (11.8 x 25.6 x 13.7 in.)
Gewicht	6.7 kg (14.8 lbs.)
Power Requirement	AC 220 - 240 V, 50/60 Hz, 0.5A
Power Consumption Maximum (Scanning)	40W or less:0.5A
Power Consumption Minimum (Ready)	10W or less
Power Consumption (Sleep)	1.8W or less
Power Consumption Power off	0.5W or less
Operating Environment	Temperature: 5°C to 35°C (41F to 95F) Humidity: 20 % RH to 80 % RH (No dewdrop)
Storage Environment	Temperature: -10°C to 50°C (14F to 122F) Humidity: 8 % RH to 75 % RH (No dewdrop)
Accessories	CD-ROM: Device driver, ISIS driver software, TWAIN driver software, User utility, Scan Button Setting Tool, Image Capture Plus with OCR Engine, Operating Manual, Control sheet // Quick Installation Guide, Power cord, USB cable, Feed tray, Mixed batch card guide
Options Roller Exchange Kit	KV-SS061
Options Roller Cleaning Paper	KV-SS03
Options Carrier Sheet	KV-SS076
Scanning Speed	ADF: Simplex: 65ppm, Duplex: 130 ipm Flatbed: 1.5s/page (A4 / Potrait, Binary / Color, (200 dpi, 300dpi)

URL: <https://business.panasonic.de/kommunikations-losungen/kv-sl3066>

CONTACT

Web: <https://business.panasonic.de/kommunikations-losungen/contact-us>